

PHOENiX ColorMeter™

Smart Color Measuring Instrument

*Accurate Color.
Smarter Decisions.*

A compact, high-performance color measurement instrument designed to deliver precise, reliable, and consistent results across a wide range of materials and industries.



D/8 Measurement Geometry

Utilizes diffuse illumination with 8° viewing geometry and SCI (Specular Component Included) to provide consistent and accurate color measurements.



Advanced Spectral Sensor

Equipped with a spectral sensor that captures reflectance data, enabling comprehensive color analysis beyond conventional tristimulus color meters.



Automatic Calibration

Features an advanced automatic calibration system to ensure consistent measurement accuracy and long-term reliability.



Cloud-Based Data Management

Measurement data can be uploaded to a cloud platform, where color information can be edited and managed.



Standalone and Connected Operation

Operates independently or connects to a mobile application or PC, displaying measurement results directly on the connected device.



Intelligent Color Matching

Identifies similar colors from a color database and supports users in uploading and managing their own color libraries.



Multi-Platform Compatibility


Compatible with Android, iOS, and Windows operating systems.



Widely used for precise color quality control in a wide range of industries



Coatings




Printing



Plastics



Textiles



Cosmetics



Food

PHOENiX ColorMeter™

Technical Specifications

Measurement System	
Measurement Geometry	D/8 (Diffuse Illumination, 8° Viewing Geometry)
Measurement Mode	SCI (Specular Component Included)
Light Source	Full-Wavelength-Balanced LED Light Source
Wavelength Range	400–700 nm
Wavelength Interval	10 nm
Measurement Aperture	8 mm
Measurement Time	Approximately 1 second
Repeatability	$\Delta E \leq 0.05$, based on 30 consecutive measurements of a white calibration tile at 5-second intervals after calibration

Color Spaces and Measurement Indices	
Color Spaces	CIE L*a*b*, CIE L*C*h°, Hunter Lab, CIE L*u*v*, XYZ, Yxy, RGB, and Munsell
Spectral Data	Spectral Reflectance
Color Difference Formulas	ΔE^*ab , ΔE^*CMC , ΔE^*94 , and ΔE_{00}
Whiteness Indices	ASTM E313-00, ASTM E313-73, CIE/ISO, AATCC, Hunter, and Taube–Berger–Stensby
Yellowness Indices	ASTM D1925, ASTM E313-00, and ASTM E313-73
Additional Functions	Blackness Index (My, dM), Staining Fastness, Color Fastness, Tint (ASTM E313-00), CMYK Color Density (A, T, E, M), Metamerism Index (MI), Opacity, and Color Strength

Illuminants and Standard Observers	
Supported Illuminants	A, B, C, D50, D55, D65, D75, F1–F12, CWF, U30, 35, DLF, NBF, TL83, and TL84
Standard Observer Angles	2° and 10°

Display and User Interface	
Display Type	IPS Full-Color Screen
Screen Size	1.14 inches
Screen Resolution	135 × 240 pixels
Operating Language	English

For more information please visit <http://www.phoenixmeter.com>

All brand and product names are trademarks of their respective owners. Specifications and external appearance are subject to change without prior notice. The actual product color may differ from that shown in this brochure. Images in this brochure are illustrative and are not actual photographs; minor differences in appearance and detail may occur. Copyright © 2026 Phoenix Sample LLC. All rights reserved. This brochure, including its contents and layout, may not be modified, adapted, reproduced in whole or in part, or incorporated into other works without the prior written permission of Phoenix Sample LLC.



Connectivity and Software Compatibility	
Interface	USB
Operating Systems	Android, iOS, and Windows
Calibration	Automatic Calibration

Power Supply	
Battery Type	Rechargeable Battery
Battery Voltage	4.2 V
Battery Capacity	760 mAh
Claimed Battery Life	Up to 10,000 continuous tests, as specified by the manufacturer

Physical Specifications	
Weight	Approximately 90 g
Dimensions	Ø31 mm × 102 mm (Diameter × Height)

